



### CPC-20B(Hard Type)

- ◆ A single-loop cutter tool, lightweight, easy to carry and operate.
- ◆ The special alloy steel blade is made for nicely cutting soft wires without breaking.
- ◆ **The max. cutting opening: D35mm.**
- ◆ Need to coordinate with hydraulic pump (automatic: CTE-25AS, manual: CP-700, or pedal: CFP-800).

### CPC-40B(Hard Type)

- ◆ A single-loop cutter tool, lightweight, easy to carry and operate.
- ◆ The special alloy steel blade is made for nicely cutting soft wires without breaking.
- ◆ **The max. cutting opening: D40mm.**
- ◆ Need to coordinate with hydraulic pump (automatic: CTE-25AS, manual: CP-700, or pedal: CFP-800).



**P.S.: It is recommended to use 5-degree blade to cut an ACSR aluminum wire.**

### CPC-55B(Hard Type)



- ◆ A single-loop cutter tool, lightweight, easy to carry and operate.
- ◆ The special alloy steel blade is made for nicely cutting soft wires without breaking.
- ◆ **The max. cutting opening: D55mm.**
- ◆ Need to coordinate with hydraulic pump (automatic: CTE-25AS, manual: CP-700, or pedal: CFP-800).

Item	Output (Ton)	Opening (mm)	Cutting Capacity										Weight (kg)
			Steel Wire(mm)		Round Bar(mm)				Stranded Conduct(mm)			Telecom Cable (mm)	
			6*7	6*12	Soft Copper Bar	Soft Aluminum Bar	Soft Steel Bar	Reinforce bar	ACSR	Copper Aluminum strand	Steel wire strand (1*9)		
CPC-20B	20	35	32	32	32	32	25	28	32	32	32	20	9.5
CPC-40B	7.1	38	25	25	24	24	16	16	38	38	20	38	3.2
CPC-55B	7.1	55	25	25	24	24	16	18	38	55	20	55	4.2



CPC-85B(Soft Type)

- ◆ A single-loop cutter tool, lightweight, easy to carry and operate.
- ◆ The special alloy steel blade is made for nicely cutting soft wires without breaking.
- ◆ The max. cutting opening: D85mm.
- ◆ Need to coordinate with hydraulic pump (automatic: CTE-25AS, manual: CP-700, or pedal: CFP-800).

CPC-100B(Soft Type)

- ◆ A single-loop cutter tool, lightweight, easy to carry and operate.
- ◆ The special alloy steel blade is made for nicely cutting soft wires without breaking.
- ◆ The max. cutting opening: D100mm.
- ◆ Need to coordinate with hydraulic pump (automatic: CTE-25AS, manual: CP-700, or pedal: CFP-800).



CPC-120B(Soft Type)

- ◆ A single-loop cutter tool, lightweight, easy to carry and operate.
- ◆ The special alloy steel blade is made for nicely cutting soft wires without breaking.
- ◆ The max. cutting opening: D120mm.
- ◆ Need to coordinate with hydraulic pump (automatic: CTE-25AS, manual: CP-700, or pedal: CFP-800).

Item	Output (Ton)	Opening (mm)	Cutting Capacity										Weight (kg)
			Steel Wire(mm)		Round Bar(mm)				Stranded Conduct(mm)			Telecom Cable (mm)	
			6*7	6*12	Soft Copper Bar	Soft Aluminum Bar	Soft Steel Bar	Reinforce bar	ACSR	Copper Aluminum strand	Steel wire strand (1*9)		
CPC-85B	5	85	—	—	—	—	—	—	—	28/38	—	85	6
CPC-100B	8.8	100	—	—	—	—	—	—	—	42/46	—	100	15.4
CPC-120B	10.6	120	—	—	—	—	—	—	—	60	—	120	10



### CC-32B+A(Soft Type)

- ◆ A single-loop cutter tool, lightweight, easy to carry and operate.
- ◆ The special alloy steel blade is made for nicely cutting soft wires without breaking.
- ◆ The max. cutting opening: D32mm (400mm<sup>2</sup>).
- ◆ Need to coordinate with hydraulic pump (automatic: CTE-25AS, manual: CP-700, or pedal: CFP-800).

### CC-50B+A(Soft Type)

- ◆ A single-loop cutter tool, lightweight, easy to carry and operate.
- ◆ The special alloy steel blade is made for nicely cutting soft wires without breaking.
- ◆ The max. cutting opening: D50mm (630mm<sup>2</sup>).
- ◆ Need to coordinate with hydraulic pump (automatic: CTE-25AS, manual: CP-700, or pedal: CFP-800).



Item	Output (Ton)	Opening (mm)	Cutting Capacity										Weight (kg)
			Steel Wire(mm)		Round Bar(mm)				Stranded Conduct(mm)			Telecom Cable (mm)	
			6*7	6*12	Soft Copper Bar	Soft Aluminum Bar	Soft Steel Bar	Reinforce bar	ACSR	Copper Aluminum strand	Steel wire strand (1*9)		
CC-32B+A	12	32	—	—	—	—	—	—	—	28	—	30	4.3
CC-50B+A	12	50	—	—	—	—	—	—	—	50	—	50	5.4